



Závity nemetrické - UNC, UNF, BSW, BSF

průměr	průměr	standardní	jemný	standardní	jemný	doporučené délky	
(inch)	(mm)	(UNC)	(UNF)	(BSW)	(BSF)	(IN)	(mm)
		s	s	s	s	3/16	4
Nr.2	2,18	56				1/4	6
Nr.4	2,84	40				3/8	9
Nr.5	3,18	40		40		1/2	12
Nr.6	3,51	32				5/8	15
5/32	3,97			32		3/4	19
Nr.8	4,17	32				7/8	22
3/16	4,75			24		1.IN	25
Nr.10	4,82	24				1.1/8	28
Nr.12	5,49	24				1.1/4	31
1/4	6,35	20	28	20	26	1.1/2	38
5/16	7,95	18	24	18	22	1.3/4	44
3/8	9,5	16	24	16	20	2.IN	50
7/16	11,1	14	20	14	18	2.1/4	57
1/2	12,7	13	20	12	16	2.1/2	63
9/16	14,3	12	18	12	16	2.3/4	69
5/8	15,9	11	18	11	14	3.IN	76
3/4	19,05	10	16	10	12	3.1/4	82
7/8	22,2	9	14	9	11	3.1/2	88
1.IN	25,4	8	14/12/	8	10	3.3/4	95
1.1/8	28,6	7	12	7		4.IN	101
1.1/4	31,8	7	12	7		4.1/2	114
1.3/8	34,9	6	12	6		5.IN	127
1.1/2	38,1	6	12	6		5.1/2	139
1.5/8	41,3			5		6.IN	152
1.3/4	44,45	5		5		7.IN	177
2.IN	50,8	4.1/2	12	4.1/2		8.IN	203
2.1/4	57,2	4.1/2		4		10.IN	254
2.1/2	63,5	4		4		12.IN	304
2.3/4	69,85	4		3.1/2		14.IN	355
3.IN	76,2	4				16.IN	406

s - počet závitů na palec (inch)

Další informace o závitech naleznete na www.killich.cz